



tesa® flameXtinct 45001

Product Information



Flame Retardant PE-Foam Tape

Product Description

The tesa® flameXtinct product family comprises a variety of high performance adhesive tape solutions for mounting applications. The tesa® flameXtinct assortment, and thus all contained products are clearly defined by following characteristics:

- Halogen-free
- High performance adhesives

tesa® flameXtinct 45001 product is a flame retardant PE-foam tape for permanent mounting in demanding applications. The tape comprises of a flame retardant acrylic adhesive and flame retardant PE-foam with excellent bonding strength.

Product Features

- Flame retardant
- Wide product portfolio
- Excellent adhesion characteristics on a variety of surfaces
- High conformability and gap filling properties
- Extremely light weight compared to alternative flame retardant bonding opportunities
- Shock absorbing
- Proven flame retardant characteristics according to FAR 25.853(a) app. F part1 and UL 94 HBF - HF1

Application Fields

- Mounting in elevator
- Bonding in aircraft cabin interior
- Assemblies in trains
- Marine applications
- Automotive

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	FR PE foam	• Total thickness	1000 µm
• Type of adhesive	FR acrylic	• Color	white
• Type of liner	plain red		



tesa® flameXtinct 45001

Product Information

Properties/Performance Values

- | | | | |
|------------------------------------|-------|-------------------------------------|-------|
| • Static shear resistance at 40°C | good | • Temperature resistance short term | 80 °C |
| • Temperature resistance long term | 80 °C | | |

Adhesion to Values

- | | | | |
|-----------------------------|-----------|-------------------------|-----------|
| • Aluminium (initial) | 16.6 N/cm | • Steel (initial) | 19.2 N/cm |
| • Aluminium (after 14 days) | 21.8 N/cm | • Steel (after 14 days) | 22 N/cm |

Additional Information

PV6 = red MOPP liner (80µm)

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=45001>