




tesa[®] 75115

Product Information



150µm d/s black flexible acrylic foam tape

Product Description

tesa[®] 75115 is a double-sided black tape consisting of a high shock absorbing black acrylic foam.

Special features:

- Thickness: 150µm
- Superior shock performance
- Good anti-repulsion properties
- Very high bonding strength
- Light blocking

Product Features

- Thickness: 150µm
- Superior shock performance
- Good anti-repulsion properties
- Very high bonding strength
- Light blocking

Application Fields

- Mounting of Displays and flexible OLED Displays
- Demanding screen and back cover mounting applications with high impact resistance
- Mounting of ultra slim bezel or curved designs

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|-------------|
| • Type of adhesive | modified acrylic | • Color | black |
| • Type of liner | PET | • Color of liner | transparent |
| • Total thickness | 150 µm | • Thickness of liner | 75 µm |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|------------------------------------|--------|
| • Static shear resistance at 23°C | very good | • Temperature resistance long term | 110 °C |
| • Static shear resistance at 40°C | very good | | |

For latest information on this product please visit <http://l.tesa.com/?ip=75115>



tesa[®] 75115

Product Information

Adhesion to Values

• Aluminium (initial)	10 N/cm	• PC (initial)	10.5 N/cm
• Aluminium (after 3 days)	12.5 N/cm	• PC (after 3 days)	11 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=75115>