




# tesa<sup>®</sup> 60735

## Product Information



tesa<sup>®</sup> 60735 50 µm black thermal management tape

### Product Description

tesa<sup>®</sup> 60735 is a 50µm transfer black thermal management tape which is designed to provide good thermal transfer efficiency for electrical devices. It offers low height deviation due to excellent appearance quality and enables direct lamination on sensitive display module substrates.

### Product Features

- Good thermal conductivity in z-direction
- Black color with excellent optical quality
- Good bonding strength
- Excellent surface wet-out
- Thin design & easy handling

### Application Fields

- Display module lamination

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |             |
|--------------------|----------|-------------------|-------------|
| • Backing          | none     | • Total thickness | 50 µm       |
| • Type of adhesive | acrylic  | • Color           | black       |
| • Type of liner    | PET film | • Color of liner  | transparent |

### Properties/Performance Values

- |                                    |          |           |      |
|------------------------------------|----------|-----------|------|
| • Breakdown voltage                | 1.4 KV   | • Wetting | 82 % |
| • Thermal conductivity z-direction | 0.4 W/mK |           |      |

### Adhesion to Values

- |                   |        |
|-------------------|--------|
| • Steel (initial) | 4 N/cm |
|-------------------|--------|

### Storage Conditions

#### Storage Conditions

- Should be stored under temperature-controlled warehouse

For latest information on this product please visit <http://l.tesa.com/?ip=60735>



# tesa® 60735

## Product Information

### Additional Information

Thermal conductivity measured by ASTM D5470

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60735>