




tesa® 60914

Product Information



140µm double sided non-woven tape

Product Description

tesa® 60914 is a 140µm double sided white translucent non-woven tape consisting of a non-woven backing and a tackified acrylic adhesive.

Product Features

- High initial adhesion
- High conformability for uneven surfaces
- High peel adhesion level on various kinds of metal, plastic, paper and film surfaces
- Good converting properties

Application Fields

- Mounting and assembly of components into electronic devices
- Permanent paper and film mounting where high peel adhesion level is needed

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|----------------|
| • Backing | non-woven | • Total thickness | 140 µm |
| • Type of adhesive | tackified acrylic | • Color | translucent |
| • Type of liner | PE-coated paper | • Color of liner | white/red logo |

Properties/Performance Values

- | | | | |
|-----------------------------------|------|--------|-----------|
| • Static shear resistance at 23°C | good | • Tack | very good |
|-----------------------------------|------|--------|-----------|

Adhesion to Values

- | | | | |
|-------------------|----------|------------------------|-----------|
| • Steel (initial) | 9.6 N/cm | • Steel (after 3 days) | 11.2 N/cm |
|-------------------|----------|------------------------|-----------|



tesa® 60914

Product Information

Additional Information

The Adhesion to Steel data is tested according to ASTM-3330

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60914>