




# tesa® 60916

## Product Information



160µm double sided non-woven tape

### Product Description

tesa® 60916 is a 160µm double sided white translucent non-woven tape consisting of a non-woven backing and a tackified acrylic adhesive.

### Product Features

- Good anti-repulsion performance
- Good bonding strength and shear resistance
- High conformability for uneven surfaces
- Good converting properties

### Application Fields

- Mounting and assembly of components into electronic devices
- Permanent paper and film mounting where high peel adhesion level is needed

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                   |                   |                |
|--------------------|-------------------|-------------------|----------------|
| • Backing          | non-woven         | • Total thickness | 160 µm         |
| • Type of adhesive | tackified acrylic | • Color           | translucent    |
| • Type of liner    | PE-coated paper   | • Color of liner  | white/red logo |

### Properties/Performance Values

- |                                   |           |        |           |
|-----------------------------------|-----------|--------|-----------|
| • Static shear resistance at 23°C | very good | • Tack | very good |
|-----------------------------------|-----------|--------|-----------|

### Adhesion to Values

- |                   |          |                        |           |
|-------------------|----------|------------------------|-----------|
| • Steel (initial) | 7.9 N/cm | • Steel (after 3 days) | 10.2 N/cm |
|-------------------|----------|------------------------|-----------|



# tesa® 60916

## Product Information

### Additional Information

The adhesion to SUS data is tested according to ASTM D3330

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60916>