

tesa® Professional 4836

Double-Sided Masking Tape

Product Information

Double sided masking tape for designing masks in all formats

Product Description

With the tesa® double sided masking tape 4836 you can design masks in all formats. This double sided masking tape is easy to use and holds protective masking material firmly in place. Adhesive on both sides of the masking tape allows you to make individual protective masks and to use it for large areas outdoors in particular. Apply the open side first to the area you wish to cover, as there is a non-adhesive area on the other side where the plastic masking foil shall be fixed to achieve large area masking protection during cleaning and renovation work like painting and plastering work.

Product Features

- Indoor and outdoor application
- Production of individual, large area masking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|--------|
| • Backing | PVC film | • Total thickness | 130 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|--------------------|------|
| • Tensile strength | 30 N/cm | • Hand tearability | good |
|--------------------|---------|--------------------|------|

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 3 N/cm |
|---------|--------|

tesa® Professional 4836

Double-Sided Masking Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4836>