




tesa® 68782

Product Information



50µm double sided black film tape

Product Description

tesa® 68782 is a black, double-sided self-adhesive tape consisting of a black PET backing and a tackified acrylic adhesive.

Product Features

- High adhesion level
- High resistance to demanding environmental conditions
- Good handling performance in converting processes

Application Fields

tesa® 68782 is used for general mounting and laminating applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-------------------|-------|----------------------|----------------|
| • Total thickness | 50 µm | • Color of liner | white/red logo |
| • Color | black | • Thickness of liner | 69 µm |

Properties/Performance Values

- | | | | |
|--------------------------|-----------|-----------------------------------|-----------|
| • Elongation at break | 50 % | • Humidity resistance | very good |
| • Tensile strength | 20 N/cm | • Static shear resistance at 23°C | good |
| • Ageing resistance (UV) | very good | | |

Adhesion to Values

- | | | | |
|-------------------------|----------|-------------------------|-----------|
| • Glass (initial) | 8.6 N/cm | • PC (after 14 days) | 9.9 N/cm |
| • Glass (after 14 days) | 9.4 N/cm | • Steel (initial) | 8.3 N/cm |
| • PC (initial) | 7.9 N/cm | • Steel (after 14 days) | 11.6 N/cm |



tesa® 68782

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=68782>