



# tesa® Professional 74921

## Self-adhesive Protection Film - Glass

### Product Information

tesa® Self-adhesive Protection Film - Glass - For large area protection of windows and other glass surfaces

### Product Description

The tesa® Self-Adhesive Protective Film – Glass is ideal for large-scale protection of glass and many other smooth surfaces. It provides effective protection against splashes and all kinds of dirt. Additionally, it protects against scratches on various smooth surfaces such as windows, window frames, mirrors, and glass doors. It is easy to apply and can be removed without leaving any residue for up to six months, making cleaning easier.

### Product Features

- Easy application
- Protects against concrete and paint spills, dirt, dust, scratches and stains
- Clean removal without leaving any residue for up to 6 months
- Repositionable multiple times
- Smooth and thin PE film

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                     |                   |       |
|--------------------|---------------------|-------------------|-------|
| • Backing          | PE film             | • Total thickness | 35 µm |
| • Type of adhesive | water-based acrylic |                   |       |

### Properties/Performance Values

- |                                |                                 |                                   |          |
|--------------------------------|---------------------------------|-----------------------------------|----------|
| • Elongation at break          | 200 %                           | • Material of masking coverage    | LDPE     |
| • Tensile strength             | 5.5 N/cm                        | • Residue-free removability       | yes      |
| • Application temperature from | -5 °C                           | • Residue-free removable after... | 180 days |
| • Application temperature to   | 60 °C                           | days                              |          |
| • Backing weight               | 29 g/m <sup>2</sup>             | • Suitable for rough surfaces     | no       |
| • Easy to remove               | yes                             | • Suitable for sensitive surfaces | yes      |
| • Humidity resistance          | good                            | • Tear resistance                 | no       |
| • Material                     | LDPE (Low-density polyethylene) | • Water resistance                | medium   |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 0.8 N/cm |
|---------|----------|



# tesa® Professional 74921

## Self-adhesive Protection Film - Glass

### Product Information

#### Storage Conditions

##### **Storage Conditions**

tesa® Self-adhesive Protection Film - Glass should be stored away from sunlight, humidity between 10% and 70%, temperature between 5°C and 30°C.

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74921>