

tesa® Professional 4460 2in1 Precision Mask

Product Information

Dual layer painter's tape for efficient paint jobs

Product Description

tesa® 4460 2in1 Precision Mask saves painters time and effort, when working with two different layers of paint, plaster or sealer. The double-layered tape need only be applied once: after using plaster, sealer or paint, the top layer is simply peeled off, revealing the second layer and ensuring clean edges, after painting.

The 2in1 Precision Mask combines two of tesa's popular precision painter's tapes with a particularly tearproof, flat Washi backing: The upper layer is tesa(R) Precision Mask Outdoor, while the second layer, offset by 1mm, to ensure optimum coverage and flat paint edges, is the tesa(R) Precision Mask Standard. The 2in1 Precision Mask is weather- and UV-resistant for 26 weeks and can be torn by hand – no scissors needed.

Product Features

*Saves time and effort: mask once, use it twice

*Easy and smooth handling due to high conformability and easy hand-tearability

- Easy removal of the top layer because of integrated fingerlift
- Ideal for sharp paint edges

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Total thickness 300 µm

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 4 % | • Sharp color edge | very good |
| • Tensile strength | 70 N/cm | • UV-resistance | 26 weeks |
| • Hand tearability | good | | |

Adhesion to Values

- Steel 1.8 N/cm

tesa® Professional 4460 2in1 Precision Mask

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4460>