



tesa® 4848 PV1



Product Information

Surface protection film

Product Description

tesa® 4848 is a self-adhesive, transparent PE film that is coated with an acrylate adhesive mass. The surface protection film is easy to use and protects sensitive surfaces (e.g. glass) from paint droplets, many chemicals, moisture, damage and contamination of any kind. The surface protection film is UV resistant, can be used for 4 weeks, and is easy to remove.

Product Features

tesa® 4848 PV1 is very versatile for indoor and outdoor applications in automotive and paint applications.

Example applications are:

- Masking of large glass areas for paint jobs
- Protection of carpets in cars

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PE film | • Total thickness | 48 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|------------------|-----|
| • Tensile strength | 12 N/cm | • Easy to remove | yes |
|--------------------|---------|------------------|-----|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 0.8 N/cm |
|---------|----------|



tesa[®] 4848 PV1

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04848>