


# tesa® 60332

## Product Information



20 µm single sided matte black single sided electrically conductive copper tape

## Product Description

tesa® 60332 is matte black single sided electrically conductive copper tape. It consists of electrically conductive matte black copper backing and single sided conductive adhesive coating layer. Designed for EMI shielding for display, FPC, MLB and other components applications.

## Product Features

- Excellent matte black appearance
- Excellent electrical conductivity in XYZ-direction
- Excellent EMI shielding performance
- Good bonding strength
- Good heat spreading performance with copper backing

## Application Fields

- Display covering and shielding
- MLB shielding
- FPC shielding
- Matte black shielding and covering on component

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                     |                      |             |
|--------------------|---------------------|----------------------|-------------|
| • Backing          | black-coated copper | • Color              | matte black |
| • Type of adhesive | conductive acrylic  | • Color of liner     | translucent |
| • Type of liner    | PET film            | • Thickness of liner | 100 µm      |
| • Total thickness  | 20 µm               |                      |             |

## Properties/Performance Values

- |  |                        |   |                  |
|--|------------------------|---|------------------|
| • Contact resistance z-direction (initial) | 0.05 Ohm / square inch | • Surface resistance x-y-direction (adhesive) | 0.1 Ohm / square |
| • Gloss level (60°)                        | 1.1 GU                 | • Surface resistance x-y-direction (backing)  | 0.1 Ohm / square |

## Adhesion to Values

- Steel (initial) 4 N/cm

# tesa® 60332

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60332>