

# tesa® 4024 PV4



## Product Information

Universal carton sealing tape

### Product Description

tesa® 4024 PV4 is a proven and reliable universal carton sealing tape for cartons up to 15 kg. It features a premium PP backing coated with a water based acrylic adhesive. The well balanced high tack and high shear resistance of the adhesive ensure a good sealing immediately after application even under more demanding environmental conditions.

### Product Features

- Smooth, low noise unwinding.
- Increased tear resistance and good immediate adhesion properties.
- Excellent ageing resistance.
- Perfect for manual tape application.

### Application Fields

Manual carton sealing tape for light and medium weight cartons up to 15 kg.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PP film	• Total thickness	50 µm
• Type of adhesive	acrylic		

### Properties/Performance Values

• Elongation at break	140 %	• Packaging Weight	Up to 15 kg
• Tensile strength	45 N/cm	• Silent unwinding	yes
• Automatic application	no	• Transport Information	Temperature 0-70°C
• Manual application	yes		

### Adhesion to Values

• Steel	2.5 N/cm
---------	----------

# tesa® 4024

## PV4

### Product Information

#### Additional Information

On request tesa® 4024 is also available as PV 5 product version with easy but noisy unwinding. This version is ideal for automated application using long rolls or for on-the-top printing.

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4024PV4>