

tesa® Professional 4363 Plastering Cloth Tape

Product Information

Plastering Cloth Tape PV2

Product Description

With the tesa® 4363 Plastering Cloth Tape you get the right tool to protect large areas during painting and plastering work. That way, you can tackle bigger tasks, without having to worry about the plastering. The tape can be removed without residue within 21 days.

Product Features

- The blue fabric tape offers improved UV resistance over its predecessor.
- The tape is easy to tear off by hand, the dense mesh offers good hand tear ability.
- The rubber adhesive works perfectly on nearly all surfaces, even rough ones.
- The robust tape lasts for up to three weeks, allowing you to tackle longer-term projects.
- Its water-repellant backing protects it from inclement weather – the right combination for outdoor plastering jobs.

Application Fields

Perfect masking tape for outdoor use during plastering and painting at construction site

- Water-repellant – rain won't loosen its adhesion
- Good in the sun – UV-resistant for up to 3 weeks
- Easy to tear off by hand, thus easy to use
- Masks and protects large areas
- Safeguards door or window frames as well as sensitive parts
- The blue tape adheres well even to rough surfaces or metal
- Tape composition: cloth backing material with rubber adhesive
- Available sizes: 25m:30mm, 25m:38mm, 25m:50mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------|-----------|
| • Elongation at break | 11 % | • Hand tearability | very good |
| • Tensile strength | 60 N/cm | • Humidity resistance | good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.6 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=4363>

tesa® Professional 4363 Plastering Cloth Tape

Product Information

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4363>