

tesa[®] tough tape

Product Information



BNR 57230, 57231

Product Description

Premium colored cloth tape with excellent adhesive strength - easy to use, for various applications.

Product Features

- For all professional solutions like handcrafts, fastening, bundling, strengthening, marking and much more
- For permanent high resilience and long-term results
- Weather-resistant for in- and outdoor applications
- Tear-resistant but tearable by hand
- Wide range of colours
- Can be written on

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing | Acrylic-coated cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------------|--------------------|-------------------------------|--|
| • Tensile strength | 100 N/cm | • Suitable surfaces | Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Adhesive strength | Very high adhesion | | |
| • Application temperature from | +10 °C | | |
| • Application temperature to | +50 °C | | |
| • Area of use | Indoor | | |
| • Humidity resistance | yes | • Tear resistance | yes |
| • Oil and grease resistance | yes | • Temperature resistance | yes |
| • Ozone resistance | yes | • Temperature resistance max. | 130 °C |
| • Residue-free removability | yes | • Temperature resistance min. | °C |
| • Solvent free | yes | • Tensibility | 13 % |
| | | • UV resistant | yes |
| | | • Waterproof | no |
| | | • Writable | yes |

Certificates

Certified according to
TLV 9027/01/06

For latest information on this product please visit <http://l.tesa.com/?cp=57230DIY>

tesa® tough tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=57230DIY>