

tesa® Powerstrips Self-Adhesive Hook L Metal Rectangular



Product Information

BNR 58266

Product Description

Large self-adhesive metal bathroom and kitchen hook for traceless removal

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 2 kg
- Removable without a trace thanks to the Powerstrips technology
- High quality design, brushed stainless steel
- Usable on tiles, glass, wood, plastic and a variety of other smooth surfaces*
- Hooks reusable with tesa Powerstrips Large

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

Application Fields

How to apply - Step by step:

1. Clean the surface with alcohol or silicone-free glass cleaner
2. Apply the Powerstrip Large strip on the surface - press for 5 seconds minimum
3. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
4. Let the hook slide down on the base plate until it is locked

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|--------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 2 Kg | | |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-----------------------------|-------------------|
| • Application temperature from | +15 °C | • Ozone resistance | no |
| • Application temperature to | +35 °C | • Residue-free removability | yes |
| • Applicationfield | Bathroom, Kitchen | • Reusable | yes |
| • Chemical Resistance | no | • Reusable with | Powerstrips Large |
| • Hazard material | no | • Solvent free | yes |
| • Material | Stainless steel | • Temperature resistance | yes |
| • Oil and grease resistance | no | • UV resistant | no |

tesa® Powerstrips Self-Adhesive Hook L Metal Rectangular

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58266>