

tesa® Professional 4613 Utility Duct Tape

Product Information

Duct tape for simple applications - available in white, black and grey



Product Description

tesa® 4613 is a duct tape that can be used for simple applications such as fastening, sealing, packing or marking, but also to aid painting jobs, for example. It comprises a natural-rubber adhesive mass and can be torn by hand. The duct tape is also suited to rough surfaces and is waterproof. tesa® 4613 is used by professional vehicle painters for such tasks as fastening cables and trim panels as well as sticking components in place. Available in black, white and grey.

Product Features

- Indoor and outdoor applications - even on rough surfaces
- Fastening of protection films
- Sealing of ducts
- Fixing, marking and packing
- Water repellent
- Easy to tear by hand
- Flexible

1

¹ *Should not be used on painted surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|-------------------|--------|
| • Backing | PE laminated cloth | • Total thickness | 180 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|-----------------------|------|
| • Elongation at break | 18 % | • Hand tearability | good |
| • Tensile strength | 30 N/cm | • Humidity resistance | good |
| • Ageing resistance (UV) | good | | |

tesa® Professional 4613 Utility Duct Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4613PRO>