

tesa® Powerbutton Hook Round, Chrome

Product Information

BNR 59342

Product Features

- · Simple and easy mounting without drilling
- Secure hold of objects up to 8 kg*
- · Chrome-plated, water-proof and temperature-resistant
- Ideally suited as a bathroom hook
- Convenient for hanging large towels or bathrobes
- Effortlessly removable without residue**

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| • | Type of adhesive | Silane modified | • | Hook shape | Round |
|---|---------------------|-----------------|---|------------|-------|
| | | polymer | | | |
| | Holding power up to | 8 Ka | | | |

Properties/Performance Values

| • | Application temperature from | +15 °C | • | Material | Chromed metal |
|---|------------------------------|-------------------|---|---------------------------|---------------|
| • | Application temperature to | +30 °C | • | Residue-free removability | yes |
| • | Applicationfield | Bathroom, Kitchen | • | Reusable | yes |
| • | Chemical Resistance | no | • | Reusable with | Adapter BK20 |
| • | Hazard material | no | • | Solvent free | yes |
| • | Humidity resistance | yes | • | UV resistant | yes |

^{*}doesn't stick to stucco, wallpaper, polyethylene, PTFE or PP

^{**}cannot be removed without residue from stucco or wallpaper



tesa® Powerbutton Hook Round, Chrome

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

