

tesa® BASIC Duct tape

Product Information

BNR 58586, 58569, 58508

Product Description

Low grade duct tape with basic tape features. The PE backing is reinforced with an 18 mesh PET fabric and coated with a tacky synthetic rubber adhesive.

Product Features

- Basic, but strong initial tack
- Adhesion to multiple materials
- Smooth hand tearability
- Handy for daily use

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------|
| • Backing | PE-film with PET-filament | • Total thickness | 150 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-----------------------------|------------------------------------|
| • Tensile strength | 30 N/cm | • Ozone resistance | yes |
| • Adhesive strength | Standard adhesion | • Residue-free removability | no |
| • Application temperature from | +10 °C | • Solvent free | yes |
| • Application temperature to | +50 °C | • Suitable surfaces | Tiles, Most plastics, Glass, Metal |
| • Area of use | Indoor | | |
| • Ecofriendly packaging | no | • Tear resistance | yes |
| • Hand tearability | yes | • Temperature resistance | yes |
| • Humidity resistance | yes | • UV resistant | yes |
| • Oil and grease resistance | no | • Waterproof | yes |
| | | • Writable | no |

tesa® BASIC Duct tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4610DIY>