

tesa® Professional 4363 Plastering Cloth Tape

Product Information

Adhesive cloth tape - 2 weeks UV-resistant

Product Description

tesa® 4363 is a waterproof adhesive cloth tape that is ideally suited to the temporary protection of window frames, door frames, façades and other sensitive surfaces. The combination of fabric (substrate) and natural rubber (adhesive mass) provides for impressive adhesive strength, even on rough surfaces. The adhesive cloth tape can be handled from temperatures as low as 5 °C, can be torn crossways and lengthways by hand, can be removed quickly and is altogether very easy to work with.

Product Features

- Outdoor masking (up to 3 weeks)
- Protection of delicate surfaces during plastering and painting
- Protection against dirt and damage through manufacturing tools and material
- Various applications in construction and house building
- Masking of window frames and facades

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------|-----------|
| • Elongation at break | 11 % | • Hand tearability | very good |
| • Tensile strength | 60 N/cm | • Humidity resistance | good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.6 N/cm |
|---------|----------|

tesa® Professional 4363 Plastering Cloth Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4363>