

tesa® Powerstrips Transparent Hooks L, White

Product Information

BNR 58812, 58811

Product Description

tesa Powerstrips Transparent Hooks Large white stand out for their striking bicolor design. They are a self-adhesive removable and reusable hanging solution.

Product Features

- Easy to mount without drilling, screws or nails
- Secure hold of up to 1 kg
- Removable without trace thanks to the Powerstrips technology
- Usable on a variety of surfaces*
- Ideal to use on glass walls and coloured surfaces due to transparency
- Hooks reusable with tesa Powerstrips Transparent Large

*Not suitable for use on styrofoam, foamed material, surfaces with non-sticking coating, porous materials

Application Fields

How to apply - Step by step: 1. Clean the surface with alcohol or silicone-free glass cleaner
2. Apply the Powerstrip Large strip on the surface - press for 5 seconds minimum
3. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
4. Let the hook slide down on the base plate until it is locked

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive	synthetic rubber	• Hook shape	Rectangular
• Holding power up to	1 Kg	• Silicone free	yes

Properties/Performance Values

• Application temperature from	+15 °C	• Residue-free removability	yes
• Applicationfield	Bathroom, Kitchen	• Reusable	yes
• Chemical Resistance	no	• Solvent free	yes
• Hazard material	no	• Temperature resistance	yes
• Material	PS (polystyrene)	• UV resistant	no
• Oil and grease resistance	no	• Waterproof	no
• Ozone resistance	no		

tesa® Powerstrips Transparent Hooks L, White

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58811>