

tesa® NOOBLESSE Robe Hook, Self-Adhesive, Stainless-Steel

Product Information

BNR 40483

Product Description

Its space-saving and beautiful design elevates the superb tesa® Nooblesse robe hook into a wonderful accessory. Application is handled with a powerful adhesive solution instead of drilling, preventing walls and tiles from harm. The hook can be removed cleanly and put back up elsewhere with a new adapter BK20.

Product Features

- Sturdy robe hook, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Noble design, round style, stainless-steel look, circular wall plate
- Secure hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Can be taken down without a trace or surface damage and re-attached with adapter BK20
- Clean, effortless mounting without drilling
- Product dimensions: 50mm x 75mm x 62mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 6 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------------|-----------------|-----------------------|--------------|
| • Applicationfield | Bathroom | • Reusable | yes |
| • Chemical Resistance | no | • Reusable with | Adapter BK20 |
| • Design series | tesa® NOOBLESSE | • Shape of wall piece | Round |
| • Material | Metal | • Solvent free | yes |
| • Number of hooks | Double | • UV resistant | yes |
| • Residue-free removability | yes | | |

tesa[®] NOOBLESSE Robe Hook, Self-Adhesive, Stainless-Steel

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=40483>