

tesa® Powerstrips Large

Product Information

BNR 58000, 58826, 58060

Product Description

tesa Powerstrips Large are self-adhesive double-sided strips. They are ideal for the removable fixation of flat objects weighing up to 2 kg to many surfaces.

Product Features

- Suitable for the whole Powerstrips Large accessory range
- Maximum hold of up to 2 kg on smooth surfaces
- Removable without trace thanks to the Powerstrips® technology
- Strong hold for objects on most surfaces*

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

- How to apply - Step by step:
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Large strip on the surface - press for 5 seconds minimum
 3. Fix object onto surface - press for 5 seconds minimum
 4. Make sure the tab can be accessed for removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 2 Kg |
| • Total thickness | 650 µm | | |

Properties/Performance Values

- | | | | |
|--------------------------------|---|-----------------------------|-----|
| • Ageing resistance (UV) | yes | • Ozone resistance | yes |
| • Application temperature from | -15 °C | • Residue-free removability | yes |
| • Applicationfield | Kitchen, Living room,
Office, Hall, Children's
room, Bathroom | • Solvent free | yes |
| | | • Temperature resistance | no |
| • Chemical Resistance | no | • UV resistant | no |
| • Hazard material | no | • Water resistance | no |
| • Humidity resistance | no | • Waterproof | no |
| • Material | _NULL | | |
| • Oil and grease resistance | no | | |

tesa® Powerstrips Large

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58000>