

5 Kg

yes

tesa® ALUXX Shower Caddy, Self-Adhesive, Chromed Aluminium



Product Information

BNR 40210

Product Description

It's child's play to put up self-adhesive tesa® Aluxx shower caddy. No drilling is needed, so tiles stay undamaged. With its glossy chrome finish, the gorgeous basket fits beautifully into your shower. Removal is possible at any time, with no trace remaining. For reuse, a new adapter BK43-2 is needed.

Product Features

• Shower caddy, with tesa® Power.Kit technology (all-in-one adhesive mounting solution) * High gloss chrome-plated aluminum, round style, circular wall plates * Reliable hold, waterproof, guaranteed stainless * Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic * Does not work on wallpaper, stucco and other surfaces with non-stick coating * Swift removal, no trace remaining, effortless reuse with new adapter BK43-2 * Convenient application, no drilling * Product dimensions: 87mm x 300mm x 147mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Silane modified

polymer

Product Construction

· Type of adhesive

| Properties/Performance Values | | | | | |
|-------------------------------|---------------------------|-------------------|---|---------------------|-----------------------|
| | Applicationfield | Bathroom | • | Reusable | yes |
| | Chemical Resistance | no | | Reusable with | Adapter BK43-2 |
| • | Curing time | 12 hour(s) | • | Shape of wall piece | Round |
| • | Design series | tesa® ALUXX | • | Solvent free | yes |
| • | Hazard material | yes | • | Suitable surfaces | Glazed Tiles, Marble, |
| • | Material | Chromed Aluminium | | | Glass, Metal, Stone, |
| • | Residue-free removability | yes | | | Concrete, Even wood, |
| | | | | | Most plastics |

Holding power up to

UV resistant



tesa® ALUXX Shower Caddy, Self-Adhesive, Chromed Aluminium

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

