

tesa® Powerstrips Waterproof Small

Product Information



BNR 59778

Product Features

- Strong hold for objects on surfaces like tiles, glass, etc.*
- Removable without a trace due to the Powerstrips Waterproof technology
- Maximum hold of up to 1kg on smooth surfaces
- Especially developed to fix objects in wet areas (e.g. shower, bathtub, etc.)
- Suitable for the Powerstrips Waterproof Small hooks

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

Application Fields

How to apply:

1. Clean the surface with alcohol or silicone-free glass cleaner
2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation - wait for 10 seconds minimum
3. Apply the Powerstrip Waterproof Small strip on the object - press for 5 seconds minimum
4. Fix object onto surface - press for 5 seconds minimum
5. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 1 Kg |
| • Total thickness | 650 µm | | |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-----------------------------|-----|
| • Ageing resistance (UV) | yes | • Oil and grease resistance | no |
| • Application temperature from | -15 °C | • Ozone resistance | yes |
| • Applicationfield | Bathroom, Kitchen | • Residue-free removability | yes |
| • Chemical Resistance | no | • Solvent free | no |
| • Hazard material | yes | • UV resistant | no |
| • Humidity resistance | yes | • Water resistance | yes |
| • Material | _NULL | • Waterproof | yes |

tesa® Powerstrips Waterproof Small

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59778>