tesa® 4903

Product Information



tesa® 4903 – CST with Paper from Responsible Sources

Product Description

tesa® 4903 is a general-purpose packaging tape based on a fine craft paper backing and a synthetic rubber adhesive. The paper backing of tesa® 4903 is made with paper from well-managed sources. The syntehtic rubber adhesive system provides very high adhesion and initial tack on a wide variety of carton qualities. tesa® 4903 is the preferred solution for light-weight packaging applications (max. 10 kg).

Product Features

- Robust backing material
- High adhesion and initial tack
- Can be torn by hand
- Printable

Application Fields

- Sealing of cardboxes
- Suitable for light-weight packaging
- Good adhesion in recycled cardboards
- Brand showcase and advertisement purposes
- Suitable for manual and automatic dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	Paper	• Total thickness	140 µm
• Type of adhesive	synthetic rubber		

Product Assortment

• Available colors	brown

Properties/Performance Values

• Elongation at break	2 %	• Low noise unwinding	yes
• Tensile strength	50 N/cm	• Manual application	yes
• Automatic application	yes	• Packaging Weight	Up to 10 kg
• Hand tearability	very good	• Solvent free	yes

For latest information on this product please visit http://l.tesa.com/?ip=4903

tesa® 4903

Product Information

Adhesion to Values

- Steel 5.5 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=4903