

tesa® 4266 PV2



Product Information

General purpose Polypropylene Carton Sealing Tape.

Product Description

tesa® 4266 is a general purpose polypropylene carton sealing tape. Suitable for use on recycled board and under shrink wrap.

Product Features

- Suitable for use on recycled board and under shrink wrap
- High volume, packaging and carton sealing requiring medium strength tape

Application Fields

- Packaging, bundling and closing
- Carton sealing
- Can be used on common hand dispensers and machines

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PP film | • Total thickness | 65 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-------------------------|---------|----------------------|-----|
| • Elongation at break | 130 % | • Hand tearability | low |
| • Tensile strength | 52 N/cm | • Manual application | yes |
| • Automatic application | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.6 N/cm |
|---------|----------|

tesa[®] 4266 PV2

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4266PV2>