

tesa® 61346

Product Information



Double-sided paper-based closing tape with fingerlift

Product Description

tesa® 61346 is a white double-sided tape with fingerlift, consisting of a paper backing and a well-balanced synthetic rubber adhesive.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- Well balanced adhesive offers high immediate adhesion on commonly used cardboard materials and very good shear strength
- Strong paper backing for reliable box closing performance
- Paper liner to withstand fast liner removal due to fingerlift without tearing
- Smooth unwinding and proven processability on market standard tape applicators
- Made with paper from well-managed certified forests and other controlled sources

Application Fields

- For closing applications of paper, cardboard, or corrugated board materials
- General purpose mounting tape
- Suitable for automatic application
- tesa® 61346 comes with a fingerlift (extended liner) for convenient liner removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|----------------------|
| • Backing | Paper | • Color | white |
| • Type of adhesive | synthetic rubber | • Color of liner | white |
| • Type of liner | glassine | • Thickness of liner | 84 µm |
| • Total thickness | 185 µm | • Weight of liner | 102 g/m ² |

Product Assortment

- Available formats SPOOL

For latest information on this product please visit <http://l.tesa.com/?ip=61346>

tesa[®] 61346

Product Information

Properties/Performance Values

• Elongation at break	1.7 %	• Solvent free	yes
• Tensile strength	40 N/cm	• Static shear resistance	very good
• Ageing resistance (UV)	low	• Static shear resistance at 40°C	low
• Humidity resistance	medium	• Tack	good

Adhesion to Values

• Steel	10 N/cm	• Steel (initial)	10 N/cm
---------	---------	-------------------	---------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61346>