

# tesa® 58314

## **Product Information**



## 25 µm PP tape for in-cell applications in EV batteries

## **Product Description**

tesa® 58314 is a light blue, linerless 25 µm Polypropylene (PP) tape with an acrylic adhesive.

It is designed for applications inside EV battery cells, offering electrolyte resistance and a PP backing. The  $25\mu m$  thin construction supports a reduction in passive materials, enabling a more efficient and compact cell architecture. Its linerless design minimizes waste and supports an efficient application process.

#### **Product Features**

- · Electrolyte resistance
- 25µm thin construction
- · Linerless design

## **Application Fields**

- Jelly-Roll Fixation
- Stack Fixation
- Cell-Tab Protection

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing	PP film	•	Total thickness	25 μm
•	Type of adhesive	acrylic			

#### **Properties/Performance Values**

•	Elongation at break	150 %	•	Electrolyte resistance	yes
•	Tensile strength	30 N/cm			

#### Adhesion to Values

Steel 1.3 N/cm



# tesa® 58314

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

