

tesa® Professional 60022

Spray Glue Extra Strong

Product Information

Extra strong film forming spray glue in a spray can with adjustable nozzle

Product Description

tesa® Spray Glue Extra Strong is a universal film-forming spray adhesive for extra firm bonding. It is an ideal fabric, wood, metal and plastic glue offering outstanding adhesion. The spray nozzle can be adjusted in 3 steps to provide the right amount of glue for smooth, rough or uneven surfaces. Use this spray to achieve permanent and temperature-resistant adhesion of a wide range of materials, such as felt, foil, foto, textiles/fabric, glass, rubber, wood, ceramic, cork, plastics, leather, metal, porcelain, stone, foam plastic or cellular rubber.

Product Features

- Suitable for heavy weight materials with rough and uneven surfaces
- Film forming spray
- Spray direction can be set either horizontal or vertical
- Adjustable spray quantity (H: high, M: medium, L: low)
- Resistant to damp and temperature from -30°C up to +80°C (short term even 100°C)
- Free from silicone

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Silicone free yes

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|-------------------------------------------|-----|
| • Adhesive strength | High adhesion | • Solvent free | no |
| • Chemical Resistance | yes | • Suitable for children of 3 years of age | no |
| • Compostable | no | • Temperature resistance | yes |
| • Hazard material | yes | • UV resistant | yes |
| • Humidity resistance | yes | • Washable | no |
| • Residue-free removability | no | • Waterproof | yes |

tesa® Professional 60022 Spray Glue Extra Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60022>