tesa® Professional 60022 Spray Glue Extra Strong

Product Information

Extra strong film forming spray glue in a spray can with adjustable nozzle

Product Description

tesa® Spray Glue Extra Strong is a film-forming adhesive for powerful, permanent bonding of heavy materials.The adjustable nozzle allows the spray volume to be adapted to smooth, rough and uneven surfaces and different applications. The silicone-free adhesive resists damp and temperatures from -30 °C to +80 °C, briefly up to +100 °C.

Product Features

- Powerful, permanent bonding over large areas
- Suitable for heavy materials and smooth to rough surfaces
- Adjustable spray volume: high, medium or low
- Horizontal or vertical spray direction
- Resistant to damp
- Temperature-resistant from -30 °C to +80 °C, short term up to +100 °C
- Silicone-free

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Silicone free	yes

Properties/Performance Values

Adhesive strength	High adhesion
Chemical Resistance	yes
Compostable	no
Hazard material	yes
Humidity resistance	yes
Recommended distance of spraying	30 cm
Residue-free removability	no
Solvent free	no
Suitable for children of 3 years of age	no
Suitable surfaces	Even wood, Stone, Brick, Acrylic glass
Temperature resistance	yes
Temperature resistance max.	80 °C
Temperature resistance min.	-30 °C
UV resistant	yes
Washable	no
Waterproof	yes

For latest information on this product please visit http://l.tesa.com/?mp=60022

tesa® Professional 60022 Spray Glue Extra Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?mp=60022