

tesa® Professional 51023 Masking Tape

Product Information

General purpose paper tape

Product Features

• The product is suitable for general purpose applications: holding, sealing, fixing, light duty packaging etc.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| • | Backing | slightly-creped paper | • | Total thickness | 110 µm |
|---|---------|-----------------------|---|-----------------|--------|
|---|---------|-----------------------|---|-----------------|--------|

Type of adhesive natural rubber

Properties/Performance Values

| • | Elongation at break | 10 % | Hand tearability | verv good |
|---|---------------------|------|--------------------------------------|-----------|

Tensile strength
 33 N/cm

Adhesion to Values

• Rough surfaces 0.6 N/cm • Steel 2 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

