

tesa® LUUP bathrobe hook, self-adhesive, chromed metal

Product Information

BNR 40292

Product Description

It's effortless to attach the self-adhesive tesa® Luup sticky wall hook to a wall. No drilling is involved, keeping walls and tiles undamaged. With its round design and glossy chrome finish, the hook is a delight to see. It can be removed quickly whenever you like and reused in another spot with a new adapter BK20.

Product Features

- Sticky wall hook, double hook, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Effortlessly removable without a trace and can be shifted elsewhere with new adapter BK20
- Convenient application without drilling
- Product dimensions: 50mm x 63mm x 70mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 6 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|-----------------------|--------------|
| • Applicationfield | Bathroom | • Reusable | yes |
| • Chemical Resistance | no | • Reusable with | Adapter BK20 |
| • Design series | tesa® LUUP | • Shape of wall piece | Round |
| • Material | Chromed metal | • Solvent free | yes |
| • Number of hooks | Double | • UV resistant | yes |
| • Residue-free removability | yes | | |

tesa® LUUP bathrobe hook, self-adhesive, chromed metal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=40292>