

# tesa® Professional 60950 / 60952

## Product Information



Anti Slip tape - black

## Product Description

tesa® 60950 is an anti slip adhesive tape with a wide range of possible applications. The anti slip tape comprises a PVC substrate coated with aluminium oxide. A strong adhesive mass of acrylate ensures safe footing on the underlying surface. The anti slip effect lasts for up to two years with ordinary use. The particularly abrasion-resistant and resilient adhesive tape is impervious to chemicals and salt water, can be torn by hand and removed again without any difficulties. It is also certified in accordance with DIN 51130. tesa® 60950 is the black version of the product.

## Product Features

- Indoor and outdoor applications
- Applications in which a secure grip underfoot is required
- Black-yellow (tesa® 60951): marking of very slippery surfaces
- Transparent (tesa® 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively
- Fluorescent (tesa® 60953): stays bright for a long period for safety and warning purposes in dark rooms

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |  |                      |        |
|--------------------|--|----------------------|--------|
| • Backing          | PVC film coated with mineral particles | • Thickness of liner | 180 µm |
| • Type of adhesive | acrylic                                | • Thickness of tape  | 720 µm |
| • Total thickness  | 900 µm                                 |                      |        |

## Properties/Performance Values

- |                       |         |                            |      |
|-----------------------|---------|----------------------------|------|
| • Elongation at break | 25 %    | • Fluorescent              | no   |
| • Tensile strength    | 30 N/cm | • Hand tearability         | good |
| • Chemical Resistance | good    | • Suitable for die cutting | yes  |
| • Easy to remove      | no      |                            |      |

## Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 5.8 N/cm |
|---------|----------|

# tesa<sup>®</sup> Professional 60950 / 60952

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60950PRO>