

tesamoll® STANDARD I-Profile

Product Information

BNR 05559

Product Description

tesamoll® Standard I-Profile is a universal wind and draught stopper tape that is ideal for insulating doors & windows by sealing gaps between 1 and 3.5 mm.

Product Features

- Self-adhesive, long-lasting foam profile
- Seals all gaps from 1 to 3.5mm
- Durability: 4 years
- Soft and flexible
- Wipe-clean

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|----------------------|--------|
| • Backing | PE | • Gap coverage up to | 3.5 mm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|-------------------|-------------------------------|--------|
| • Chemical Resistance | no | • Solvent free | yes |
| • Durability | 4 years | • Temperature resistance | yes |
| • Humidity resistance | no | • Temperature resistance max. | 50 °C |
| • Material | PE (polyethylene) | • Temperature resistance min. | -50 °C |
| • Residue-free removability | no | | |

tesamoll® STANDARD I-Profile

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5559>