

tesa® Mounting Tape for Tiles & Metal

100 kg/m



Product Information

BNR 77746, 77747

Product Description

Mounting Tape for Tiles & Metal up to 100kg/m. The strongest way to wall-mount on smooth and solid surfaces like tiles.

Product Features

- For smooth and solid surfaces like tiles indoors
- Can hold up to 100kg/m*
- For permanent applications

*For optimal results a max. of 6kg per application/objects is recommended

Application Fields

- How to apply – Step by step 1. For the best possible bond, use alcohol or silicone-free window cleaner to make sure your surface is free of dust and grease. Ensure the surface is dry before application.
2. Check whether the surface or the object is rougher and apply the mounting tape to it.
3. Apply the heavy-duty, double-sided tape in vertical strips corresponding to the full length of the object or surface, and press down firmly all along the entire strip for at least 5 seconds. Be careful not to touch the exposed adhesive area.
4. Remove the backing from the tape and position the item on the surface.
5. Press down firmly on the item for at least another 5 seconds to get as close a bond as possible.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------------------|----------|
| • Backing | PE foam | • Total thickness | 1100 µm |
| • Type of adhesive | synthetic rubber | • Holding power of tape up to | 100 KG/M |

Properties/Performance Values

- | | | | |
|--------------------------------|--------|---------------------|--|
| • Application temperature from | -10 °C | • Solvent free | yes |
| • Humidity resistance | no | • Suitable surfaces | Even wood, Tiles,
Most plastics, Glass,
Acrylic glass, Steel,
Metal |
| • Residue-free removability | no | | |

tesa® Mounting Tape for Tiles & Metal

100 kg/m

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=77746>