

# tesa® Powerbutton Universal Hook L

## Product Information

BNR 59322

### Product Description

The tesa® Powerbutton Universal hook Large is a water- and heat-resistant chrome hook with technology for easy mounting without drilling.

### Product Features

- Easy application without drilling, screws or nails
- Extra-strong hold up to 8kg
- Strong hold on most surfaces\*
- Usable on and removable from most surfaces\*\*
- Waterproof
- High temperature resistance
- Chrome Plated
- Hooks reusable with the tesa® Powerbutton technology

\*Does not hold Plaster, Wallpaper, PE, PTFE or PP

\*\*Not removable from Plaster or Wallpaper. Residues might remain

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                       |                         |              |       |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive    | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 8 Kg                    |              |       |

### Properties/Performance Values

- |                                |                   |                             |               |
|--------------------------------|-------------------|-----------------------------|---------------|
| • Application temperature from | +15 °C            | • Material                  | Chromed metal |
| • Application temperature to   | +30 °C            | • Residue-free removability | yes           |
| • Applicationfield             | Bathroom, Kitchen | • Reusable                  | yes           |
| • Chemical Resistance          | no                | • Solvent free              | yes           |
| • Hazard material              | no                | • UV resistant              | yes           |

# tesa® Powerbutton Universal Hook L

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59322>