

tesa® Professional 74921

Self-adhesive Protective Film – Shields Glass from Dust & Scratches

Product Information

tesa® Self-adhesive Protection Film - Glass - For large area protection and coverage of various plain surfaces

Product Description

This protective PE film shields windows, mirrors, and smooth surfaces from dust, scratches, and stains. It is reusable, cuttable, and removable without residue for up to 6 months. Ideal for renovations, painting, and construction work. Suitable for indoor and outdoor use, it helps keep surfaces clean and damage-free during any project.

Product Features

- Protects surfaces from dust, scratches, and stains – ideal for glass and mirrors
- Easy to apply and remove without residue for up to 6 months
- Suitable for indoor and outdoor use – simple to cut to size
- Reusable multiple times – keeps surfaces clean
- Effective surface protection – perfect for painting and renovation work

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | PE film | • Total thickness | 35 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------------|---------------------------------|-----------------------------------|----------|
| • Elongation at break | 200 % | • Material of masking coverage | LDPE |
| • Tensile strength | 5.5 N/cm | • Residue-free removability | yes |
| • Application temperature from | -5 °C | • Residue-free removable after... | 180 days |
| • Application temperature to | 60 °C | days | |
| • Backing weight | 29 g/m ² | • Suitable for rough surfaces | no |
| • Easy to remove | yes | • Suitable for sensitive surfaces | yes |
| • Humidity resistance | good | • Tear resistance | no |
| • Material | LDPE (Low-density polyethylene) | • Water resistance | medium |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 0.8 N/cm |
|---------|----------|

tesa® Professional 74921

Self-adhesive Protective Film – Shields Glass from Dust & Scratches

Product Information

Storage Conditions

Storage Conditions

tesa® Self-adhesive Protection Film - Glass should be stored away from sunlight, humidity between 10% and 70%, temperature between 5°C and 30°C.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74921>