

tesa® 64706

Product Information



PVC closed cell single sided foam tape 6.4mm thick (black)

Product Description

tesa® 64706 foam tape consists of a closed cell polyvinyl chloride (PVC) foam backing with an acrylic adhesive on one side. The closed cell foam can create a dust and moisture seal when compressed and is conformable to help seal uneven surfaces.

Product Features

- Adheres to wide variety of surfaces
- Resistant to moisture and UV
- Foam backing will absorb sound and dampen vibration
- Compressible foam can be used for die cutting and gasket

Application Fields

- Vibration dampening and sealing in building construction
- Vibration dampening and sealing for transport applications
- Sealing access panels on industrial machinery
- Sealing electrical housings, enclosures, and cabinet doors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing | PVC foam | • Total thickness | 6.4 mm |
| • Type of adhesive | acrylic | • Color | black |
| • Type of liner | coated paper | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|------------------------------------|------------|
| • Elongation at break | 130 % | • Temperature resistance max. | 90 °C |
| • Tensile strength | 20 N/cm | • Thermal conductivity z-direction | 0.037 W/mK |
| • Hardness - Shore 00 | 35 STK | | |

Additional Information

- Foam density: 180 kg/m³ ASTM D792
- Foam compression set (50%): ≤10% ASTM D1056
- Foam 25% compression strength: 30 kPa ASTM D1056
- Fire resistance: FMVSS 302

tesa® 64706

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64706>