
tesa® 73817

Product Information



350µm double sided acrylic foam tape

Product Description

tesa® 73817 is a black double-sided tape consisting of a high shock absorbing acrylic foam backing and easy activation adhesive on both sides.

Product Features

- Excellent easy-activation performance even on the rough surface.
- Superior shock resistance
- Superior anti-repulsion performance
- Reliable bonding performance on rough substrate under low pressure
- High sealing ability with superior waterproofness

Application Fields

- Demanding lens or screen and back cover mounting applications with high requirements for impact resistance.
- Mounting of components with critical demand on impact resistance, e.g. speaker, battery
- Mounting of waterproof designs, e.g. Camera lens mounting
- Mounting of 3D curved or ultra slim bezel designs.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing	Acrylic foam	Color	black
Type of adhesive	tackified acrylic	Color of liner	transparent
Type of liner	PET film	Thickness of liner	50 µm
Total thickness	350 µm		

Properties/Performance Values

Static shear resistance at 23°C	very good	Static shear resistance at 40°C	very good

Adhesion to Values

Glass (initial)	18.1 N/cm	PC (after 3 days)	29.7 N/cm
Glass (after 3 days)	19.3 N/cm	Steel (initial)	16.8 N/cm
PC (initial)	20.2 N/cm	Steel (after 3 days)	19.3 N/cm

For latest information on this product please visit http://l.tesa.com/?ip=73817

tesa® 73817

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=73817