

# tesa® 51638 PV0VN



## Product Information

PET fleece tape with water-based acrylic adhesive

## Product Description

tesa® 51638 is a tape for wire harness covering that is applied on passenger compartment harnesses. It combines important features as noise damping, abrasion resistance and bundling strength while keeping harnesses flexible, therefore supporting an easy harness assembly process at the OEM.

tesa® 51638 is a PET fleece wire harness tape with a water-based acrylic adhesive that is optimized for manual application.

## Product Features

- Noise damping performance
- Basic abrasion resistant performance
- flexible and smooth appearance
- Tear resistant for secure bundling of harnesses
- Stable unwind force for constant behavior when applying
- Ageing resistance performance
- Hand-tearable for quick application
- Low odor
- Color: Black

## Application Fields

tesa® 51638 is designed to provide good noise damping and secure bundling performances on the harness. The tape is mainly applied on harnesses for the passenger compartment, and the harness remains flexible after applying the tape.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |            |                   |        |
|--------------------|------------|-------------------|--------|
| • Backing          | PET fleece | • Total thickness | 260 µm |
| • Type of adhesive | acrylic    |                   |        |

## Properties/Performance Values

- |   |           |                                   |                       |
|---|-----------|-----------------------------------|-----------------------|
| • Elongation at break                       | 19.2 %    | • Temperature resistance max.     | 105 °C                |
| • Tensile strength                          | 46.4 N/cm | • Temperature resistance min.     | -40 °C                |
| • Abrasion resistance (10mm mandrel, LV312) | Class B   | • Unwind force (roll width < 9mm) | 4.5 N/roll (30 m/min) |
| • Abrasion resistance (5mm mandrel, LV312)  | Class A   | • Unwind force (roll width > 9mm) | 9 N/roll (30 m/min)   |
| • Noise damping (LV312)                     | Class C   |                                   |                       |

# tesa<sup>®</sup> 51638 PV0VN

## Product Information

### Adhesion to Values

- Steel 2.3 N/cm

### Additional Information

- Standard widths: 9, 19, 25, 32 mm
- Standard lengths: 25 m
- Most combinations of width and length are possible
- Further dimensions are available upon request

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

