


tesa® 88710S OCA



Product Information

250µm Optically Clear Adhesive for Automotive Applications

Product Description

Our new 250µm optically clear tesa® OCA 88710S is specially developed for automotive displays. It provides excellent protection against contamination, helping to minimize defects during lamination process.

Product Features

- Efficient particle coverage capability
- Outstanding Q-Sun stability (DIN 75220)
- High transmittance with low haze
- Robust adhesive properties
- Balanced lamination with reliable performance

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|----------------------|-------------|
| • Backing | none | • Color | transparent |
| • Type of adhesive | acrylic | • Color of liner | transparent |
| • Type of liner | PET film | • Thickness of liner | 100 µm |
| • Total thickness | 250 µm | | |

Product Assortment

- | | | | |
|-------------------------|-------------|---------------------|------------------|
| • Available thicknesses | 250 µm | • Available formats | LOG ROLL TRIMMED |
| • Available colors | transparent | • Available liners | PET film |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|--------------------|------|
| • Haze | 0.001 % | • Refractive index | 1.48 |
| • Humidity resistance | very good | | |

Adhesion to Values

- Glass (covered side, after 1 day) 18 N/cm

tesa® 88710S OCA

Product Information

Storage Conditions

Storage Conditions

Temperature: From +5°C to +30°C

Relative humidity: From 30% to 60%

Precautions: Protect for direct sun light, do not store outside

Other storage advice: Storage of rolls in a horizontal position. Avoid mechanical impacts and short overheating, if removed from cold storage, ensure no condensation on packaging.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88710S>