

tesa® Professional 4348 Painters' Tape



Product Information

Flexible masking tape for indoor painting applications

Product Description

tesa® 4348 is a slightly creped, tear-resistant standard masking tape with a natural rubber adhesive mass that is perfectly suited to indoor painting tasks. The supple masking tape can be torn by hand, used for up to 7 days, and is easy to remove after use. Thanks to its excellent adhesive strength, it enables clearly-defined edges during painting work and is a reliable tool for professional painters.

Product Features

- Indoor applications
- Clean edges to paint and lacquer
- For smooth surfaces
- For simple painting tasks

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 10 % | • Hand tearability | very good |
| • Tensile strength | 36 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.3 N/cm |
|---------|----------|

tesa® Professional 4348 Painters' Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4348>