

tesa® Professional 4402

Precision Standard

Product Information

Standard Precision masking tape with masking foil

Product Description

With the masking film of tesa Easy Cover® 4402 (incl. tesa® 4344 Precision Mask® Standard) you will save both time and effort. Because with the practical 2-in-1 solution you can protect your surroundings quickly and safely in only one working step. Cover up even large surfaces in no time – furniture, floors or walls – thanks to the straightforward handling of the different formats. With tesa Easy Cover® 4402 Precision Standard, you are well equipped to pave the way for outstanding painting work. In combination with your skilled craftsmanship, you will achieve results that will impress your customers.

Product Features

- Time-saving 2-in-1 covering solution for top professionals: covering large areas and accurate masking in one step
- Combination of masking film and integrated tesa® precision crepe
- For flat and precise paint edges
- Long-term application on smooth and slightly structured surfaces (up to 3 months)
- Ideal foundation for excellent indoor paint jobs

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------------------|------|
| • Elongation at break | 4 % | • Material of masking coverage | HDPE |
| • Tensile strength | 30 N/cm | • Suitable for rough surfaces | good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.7 N/cm |
|---------|----------|

tesa® Professional 4402

Precision Standard

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4402>