

tesa® Professional 4319 Masking Tape for Curves

Product Information

Flexible masking tape for paint work - especially for curves

Product Description

With the tesa® flexible masking tape you will ace every curve. The quality of the crepe allows this flexible masking tape to be adapted perfectly to any curvature. Thanks to the thick adhesive padding, this flexible masking tape holds reliably even on rough surfaces, thus avoiding ugly paint tears. The curves specialist from tesa® makes perfect painting work possible even under difficult conditions. With the combination of high-quality surface protection tape and sound workmanship you will achieve optimum working results. The flexible masking tape saves you corrections that are time-consuming.

Product Features

- Masking during lacquering and painting work
- For under body repair and extreme curves
- Rapid, reliable masking off, even on rough surfaces
- Sealing and bundling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|--------|
| • Backing | highly-creped paper | • Total thickness | 375 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 58 % | • Hand tearability | very good |
| • Tensile strength | 28 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 4.5 N/cm |
|---------|----------|

tesa® Professional 4319 Masking Tape for Curves

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4319C>