

tesa® extra Power Removable Repair

Product Information

56432, 56431

Product Description

If you are looking for a tape that sticks reliably and removes cleanly without residue, this cloth tape is the perfect choice. Ideal for all your home projects, from quick fixes to lasting solutions.

Sustainable Aspects

Consisting of 51% renewable materials, such as natural rubber (excluding packaging and core), this tape contributes to sustainability without compromising performance.

Product Features

- · Residue-free removal: leaves no adhesive traces
- Strong hold: ideal for repairing, fastening and reinforcing even on rough surfaces
- Easy to use: hand-tearable and writable
- · Contributing to sustainability: tape consists of 51% renewable materials, such as natural rubber
- · Available in black, white and grey

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

	T (11)		T	000
•	Type of adhesive	natural rubber	 Total thickness 	280 um

Properties/Performance Values

 Elongation at break Tensile strength Abrasion resistance Adhesive strength Area of use Hand tearability 	9 % 70 N/cm very good High adhesion Indoor very good	Solvent freeSuitable surfaces	yes Acrylic glass, Brick, Cardboard, Glass, Metal, Paper, Plaster, Steel, Stone, Tiles, Wood
 Residue-free removability 	very good yes	Tear resistance	yes
• Residue-free removability	yes	Temperature resistance	yes
		•	•
		Water resistance	yes
		 Writable 	yes



tesa® extra Power Removable Repair

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

