tesa® 60433

Product Information

Clear BOPP Packaging Tape

Product Description

tesa® 60433 features a highly transparent polypropylene film backing combined with a versatile water-based acrylic adhesive, making it an effective solution for lightweight packaging applications up to 20 kg. The product is distinguished by its smooth unwinding properties. tesa® 60433 is particularly well-suited for sealing lightweight cartons that require high transparency.

Product Features

- Clear color with excellent transparency
- Versatile water based acrylic adhesive
- Smooth unwinding

Application Fields

- Carton sealing for light weight cartons up to 20 kg
- For manual and automated application
- Packaging applications where high transparency is needed

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	BOPP	• Total thickness	50 µm
• Type of adhesive	water-based acrylic		

Product Assortment

• Available colors	transparent	• Available formats	BARREL / DRUM

Properties/Performance Values

• Elongation at break	160 %	• Manual application	yes
• Tensile strength	40 N/cm	• Packaging Weight	Up to 20 kg
• Ageing resistance (UV)	medium	• Printability	no
• Automatic application	yes	• Silent unwinding	no
• Core diameter	3	• Suitable for dangerous goods	yes
• Hand tearability	no	• Suitable for deep freezing	no
• Low unwinding force	good	• Transport Information	Temperature 0-70°C

For latest information on this product please visit http://l.tesa.com/?ip=60433

tesa® 60433

Product Information

Adhesion to Values

- Steel 2.8 N/cm

Storage Conditions

Storage Conditions
Temperature : < 40°C (advice)

Relative humidity : from 10% to 90%

Precautions : protect for direct sun light, do not store outside

Other storage advices : avoid mechanical impacts and short overheating; package is available;

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=60433