

tesa® Professional 4453 Precision Mask Medium Sensitive

Product Information

High grade paper masking tape for precise paint edges on moderately sensitive surfaces

Product Description

tesa® 4453 Precision Mask Medium Sensitive offers professional painters and decorators a cost-effective solution for masking moderately sensitive surfaces. With its balanced adhesive strength, it provides secure adhesion without compromising surface integrity on most delicate substrates. The tape's adaptable, high grade paper backing ensures sharp paint lines and easy removal. Its purple colour stands out on the job site, and it is suitable for indoor masking up to two months and outdoor applications up to three weeks. Additionally, it is made from paper sourced from responsibly managed forests, promoting sustainability in its production.

Sustainable Aspects

tesa® 4453 Precision Mask Medium Sensitive is made with paper from well-managed, certified forests and other controlled sources

Product Features

- Indoor masking (up to 2 months)
- Outdoor masking (up to 3 weeks)
- Suitable for moderately sensitive and delicate surfaces
- · Balanced adhesive strength for secure hold
- · Strong but conformable paper backing for sharp, flat paint edges
- · Easy and clean removal
- · Made with paper sourced from responsibly managed forests and other controlled sources

Application Fields

- · Masking of moderately sensitive and delicate surfaces
- · Protection of surfaces during painting work

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing
Washi paper
Total thickness
73 μm

Type of adhesive water-based acrylic



tesa® Professional 4453 Precision Mask Medium Sensitive

Product Information

Properties/Performance Values

 Elongation at break 10 % · Paint anchorage very good Tensile strength 31 N/cm · Residue-free removability yes Area of use In- and Outdoor · Sharp color edge very good Easy to remove · Solvent free yes Suitable for sensitive surfaces Hand tearability very good good

Adhesion to Values

Steel 1 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

