

tesa® 5225 Crack Cover

Product Information

Flexibe fleece tape for surface preparation prior to painting and wallpapering

Product Description

When painting or wallpapering during a renovation, achieving a perfectly smooth and crack-free surface is crucial for flawless results. tesa® Crack Cover is a highly flexible fleece tape specifically designed for repairing cracks in walls and ceilings. It's also perfect for drywall crack repairs and helps fix various imperfections on wall surfaces. This thin self-adhesive tape is ideal for covering cracks, seams, and holes, making minor imperfections disappear and ensuring that a fresh coat of paint won't reveal unsightly cracks soon after application.

Product Features

- Covers cracks and seams seamlessly
- Self-adhesive
- Minimal elevation
- Flexible material compensates for substrate stress
- Paint, plaster, and wallpaper can be applied immediately after use
- Supports efficient work process

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|-------------------|--------|
| • Backing | non-woven | • Total thickness | 110 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|-----------------------------|-----|
| • Tensile strength | 16 N/cm | • Residue-free removability | no |
| • Hand tearability | good | • UV resistant | yes |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.1 N/cm |
|---------|----------|

tesa® 5225 Crack Cover

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=5225>