

# tesa<sup>®</sup> INSULATION Weatherstrip Silicone One Size Fits All



## Product Information

5417

## Product Description

The tesa<sup>®</sup> INSULATION Weatherstrip PREMIUM sealing tape protects your home from cold, heat, and noise. Durable material and strong adhesive power for up to 15 years. Ideal for windows and doors. UV and temperature resistant.

## Product Features

- Enhanced living comfort through gap sealing
- Silicone seal for gaps from 1 to 7 mm - universally applicable for all gap widths
- Self-adhesive - easy installation
- Durability: 15 years
- Extremely high weather, UV, and ozone resistance
- High temperature resistance from -50°C to +60°C
- Air and water impermeable
- Transparent
- Easy to clean

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                      |      |
|--------------------|------------------|----------------------|------|
| • Backing          | Fabric           | • Gap coverage up to | 7 mm |
| • Type of adhesive | synthetic rubber |                      |      |

## Properties/Performance Values

- |                             |          |                               |        |
|-----------------------------|----------|-------------------------------|--------|
| • Chemical Resistance       | no       | • Solvent free                | yes    |
| • Durability                | 15 years | • Temperature resistance      | yes    |
| • Material                  | Silicone | • Temperature resistance max. | 60 °C  |
| • Residue-free removability | no       | • Temperature resistance min. | -20 °C |

# tesa<sup>®</sup> INSULATION Weatherstrip Silicone One Size Fits All

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5417A>