

tesa® 4619PRO

Duct Tape+

Product Information

tesa® Duct Tape+ (4619) – 2-Pack

Product Description

Duct Tap+ is your go-to tape for tough repair and sealing jobs. The practical 2-roll format is built for repeated use, combining strong grip with fast handling. With a robust PE backing and weather-resistant adhesive, it adheres well to rough surfaces and can be used indoors or outdoors. Tearable by hand, it's perfect for quick fixes and reliable bonds, job after job.

Product Features

- Reliable solution for day-to-day fixing: Designed for quick application and effortless hand-tearability – ideal when time and efficiency matter
- Multipurpose use across environments: From sealing to bundling or basic repair tasks, this duct tape handles smooth and slightly uneven surfaces with ease
- Suitable for indoor and temporary outdoor jobs: Its adhesive strength and moisture resistance make it a go-to option for short-term, versatile applications
- Smooth handling experience: Easy unwinding and flexible backing ensure seamless use without disruptions
- Great value with twin-pack format: Includes 2 rolls – practical for frequent use and professional restocking

Application Fields

- Sealing or reinforcing light packaging or temporary coverings
- Fastening or bundling lightweight items, tools, or accessories
- General-purpose masking or surface protection indoors
- Quick temporary repairs in workshops, warehouses, or on site
- Holding, labelling, or marking during short-term applications
- Supporting ad hoc fixes in maintenance or facility operations

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Type of adhesive | synthetic rubber | • Total thickness | 170 µm |
|--------------------|------------------|-------------------|--------|

tesa® 4619PRO

Duct Tape+

Product Information

Properties/Performance Values

• Elongation at break	10 %	• Residue-free removability	no
• Tensile strength	40.1 N/cm	• Solvent free	no
• Abrasion resistance	yes	• Tear resistance	yes
• Adhesive strength	High adhesion	• Temperature resistance	good
• Hand tearability	good	• UV resistant	yes
• Humidity resistance	yes	• Waterproof	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4619PRO>